

RL25H Set

CST/berger


The robust solution for precise outdoor leveling



- ▶ Self-leveling: horizontal
- ▶ Robust design to protect against vibrations and falls
- ▶ High precision and long range for outdoor applications

Additional features

- ▶ Efficient protection against dust and splash water
- ▶ Manual single-slope capability of $\pm 8\%$ to enable more versatility on the jobsite
- ▶ User-friendly keypad design



Applications

- ▶ Excavation, structural work, formwork
- ▶ Elevation marking, bricklaying, transferring heights
- ▶ Landscaping
- ▶ Screeding
- ▶ Alignment in terrain

Scope of delivery

- RD5 laser receiver with bracket ✓
- NMB1 Rechargeable Battery ✓
- CHNM1 charger ✓
- Hard carry case ✓



Technical specifications

RL25H Set

Part number	F 034 061 ONE
Laser diode	635 Nm
Laser class	2
Working range with laser receiver.....	225 m (radius)
Accuracy	± 0.08 mm/m horizontal
Self-leveling range	$\pm 5^\circ$
Dust and splash protection	IP56
Rotation Speed	600rpm
Power supply	3 x 1.5 V LR20 (D) or 2 x 1.2 V HR20 (D) NiMH batteries)
Operating time (max.).....	Non-rechargeable batteries 85h Rechargeable batteries (NiMH) 30 h
Tripod connection	5/8"
Length	200 mm
Width	220 mm
Height	190 mm
Weight	2.3 kg