



**Geo Levels No. 10**

Robust and reliable. The No. 10 level series, a market leading product range for more than 15 years. Continuous development ensures the No. 10 is up-to-date and suitable for all levelling applications.

- Suitable for builders, engineers and surveyors.
- Bubble reading prism for convenient observation of bubble at eye level
  - Optical sight for fast alignment to target
  - Robust metal housing for protection against



<i>Model</i>	<i>No. 10-20</i>	<i>No. 10-22</i>	<i>No. 10-26</i>	<i>No. 10-32</i>
Mean error for 1 km double levelling	2,5 mm	2,5 mm	2,0 mm	1,5 mm
Telescope magnification	20 x	22 x	26 x	32 x
Objective diameter	35 mm	35 mm	40 mm	40 mm
Field of view at 100 m	3,5 m	3,5 m	3,5 m	3,5 m
Shortest focussing distance	0,5 m	0,5 m	0,5 m	0,5 m
Working range of compensator	±15'	±15'	±15'	±15'
Levelling accuracy	±0,5"	±0,5"	±0,5"	±0,5"
Circular bubble	8' /2 mm	8' /2 mm	8' /2 mm	8' /2 mm
Horizontal circle	360°	360°	360°	360°
Dust/water protection	IP 54	IP 54	IP 54	IP 54
Weight	1,8 kg	1,8 kg	1,8 kg	1,8 kg

**Unit 7 - 7 Prindiville Drive  
Wangara, Western Australia 6065  
Phone: +61 8 9409 4058  
Fax: +61 8 9409 4068**

**[www.gsrlasertools.com.au](http://www.gsrlasertools.com.au)**

Email : [sales@gsrlasertools.com.au](mailto:sales@gsrlasertools.com.au)