



Geo FKL-50 Pipe Laser

Self-levelling pipe laser. A rugged waterproof construction for long lasting performance and reliability in the toughest conditions.



Features

- Robust aluminium housing
- Easy intuitive operation
- Fully automatic self-levelling
- Automatic beam centring
- Laser start point indication
- Clear easy to read illuminated LCD display
- Integrated rechargeable batteries
- Remote control

Technical Data

Laser class	3R
Laser diode power	< 2 mW
Beam diameter	12 mm
Working range up to	200 m
Grade range	-20 % – +40 %
Self-levelling range	± 5°
Minimum display reading	0,001%
Horizontal accuracy	± 5 mm/100 m
Left/right scanning	± 4°
Operating time	24 h (NiMH)
Temperature range	-20 °C – +50 °C
Power supply	4 x D 8000 mAh NiMH
Optional	4 x D Alkaline
Remote control range	front 10m / back 60 m
Dust/water protection	IP 68
Dimensions	Ø 132 mm, L = 380 mm
Weight (laser only)	5 kg
Weight set	11 kg



Fittings

- Target frame with target
- Container
- Pipe Laser
- Remote control
- Leg set DN 500
- Leg set DN 400
- Leg set DN 300
- Leg set DN 200
- Leg set DN 150
- Adapter for 3 leg set up
- Charger
- Batterie case for alkaline batteries
- Target DN 400 – 500

**Unit 7 - 7 Prindiville Drive
Wangara, Western Australia 6065
Phone: +61 8 9409 4058
Fax: +61 8 9409 4068**

www.gsrlasertools.com.au

Email : sales@gsrlasertools.com.au