



## ***Geo FL 40-4 Liner***

***The starter model for professionals!***

Using the latest laser diode technology to ensure optimum line visibility. 3 laser crosses at 90° to each other connected by a horizontal laser line.

### **Features :**

- 1 horizontal and 3 vertical laser lines
- Shut-off of self-levelling function for manual use (slope)
- Locking device for safe transport
- Magnetic connection from instrument to wall mount
- Centering adapter for optimum positioning over a floor point
- Visual and audible alarm when out of level
- Use with receiver FR 55/FR 55-M (optional) to extend the working range up to 30 m



### **TECHNICAL DATA**

Self-levelling range	± 3,5°
Accuracy	± 3 mm/10 m
Working range without receiver	20 m*
Working range with receiver	30 m
Operating time	12 h
Power supply	3 x 1.5 V AA
Visible laser diodes	4 x 635 nm
Laser class	3R
Weight	1,0 kg


\* depending on room illumination



### **SUPPLIED WITH**

Wall/tripod mount with 5/8" thread, set of batteries, magnetic target, laser intensive glasses, padded carrying case

Centering adapter :  
Find Your Floor marking Point easy



**Unit 7 - 7 Prindiville Drive  
Wangara, Western Australia 6065  
Phone: +61 8 9409 4058  
Fax: +61 8 9409 4068**

**[www.gsrlasertools.com.au](http://www.gsrlasertools.com.au)**

Email : [sales@gsrlasertools.com.au](mailto:sales@gsrlasertools.com.au)