



Leica Lino L2+ Extra long lines

Simply perfect all along the line! The super cross.

Specification & Description



Emergence angle of 180°
Pulse function with power-saving mode
Modern, ergonomic housing
Exact 90° angle
Very easy to use




The time-consuming and tedious drawing of lines on the wall is a thing of the past. The Leica Lino L2+ projects them exactly, quickly and easily allowing you to concentrate on the job in hand. The improved emergence angle ensures outstanding visibility and extension of the laser lines and allow perfect levelling and alignment at long distances.

Emergence angle of 180°. Pulse function with power-saving mode. Modern, ergonomic housing. Exact 90° angle. Very easy to use.



Self-levelling

The instrument is set up quickly and effortlessly to project horizontal or vertical lines. Minor angular miss-alignments of $\pm 4^\circ$ are compensated automatically. If the tilt is outside these limits, the device does not project any lines and errors are therefore prevented.



Working in bright conditions

The pulse function is not just an energy-saving mode: it also allows you to locate the laser lines using a laser detector, even in very bright lighting conditions. A series of acoustic signals from the detector indicates the precise position of the laser beam plane.



Lock function

You can manually switch off the self-levelling features using the lock function. The laser line can then be projected at any angle. The lock function also serves as transport protection

**Unit 7 - 7 Prindiville Drive
Wangara, Western Australia 6065**

Phone: +61 8 9409 4058

Fax: +61 8 9409 4068

www.gsrlasertools.com.au

Email : sales@gsrlasertools.com.au



Technical specifications:	
Range	up to 15 m depending on lighting conditions
Range with detector (Optional)	> 30 m
Levelling accuracy @ 5 m	± 1.0 mm
Self-levelling range	4° ± 0.5°
Accuracy of horizontal line @ 5 m	± 1.5 mm
Vertical accuracy @ 3 m line length	± 0.75 mm
Beam divergence	< 180°
Laser type	635 nm, laser class II
Batteries	type AA 4 × 1.5 V
Protection class splash water/ dust proof	IP54
Operating temperature	-10 °C to 40 °C
Storage temperature	-25 °C to 70 °C
Dimensions (H × D × W)	117.8 × 130.7 × 75.4 mm
Weight without batteries	370 g
Tripod thread	¼"



Scope of Delivery :
 Magnetic adaptor, Target plate, Batteries, Manual,
 Belt pouch, Quick start guide, Safety manual, User
 manual CD & Hard case



Laser Receiver available for outdoor usage - Please see Leica
 Receiver LLD2
 Available with or without receiver holder



Unit 7 - 7 Prindiville Drive
Wangara, Western Australia 6065
Phone: +61 8 9409 4058
Fax: +61 8 9409 4068

www.gsrlasertools.com.au

Email : sales@gsrlasertools.com.au