



SMART

IT COULD NOT BE MORE SIMPLE

Simply set up and switch on: The compact crossline laser immediately projects two accurately placed, bright laser lines in the room.



FEATURES

- Particularly easy and safe operation even for the less experienced users
- Compact, lightweight, handy Bright, very visible laser lines Broad line spread gives a large working area

APPLICATIONS

Horizontal Levelling
Vertical Levelling

SMART

PERFECT INSTALLATION ON ANY WALL

Whether putting up shelves, fitting kitchen cupboards or hanging pictures - the SMART helps you in all these situations, making it your "go-to" for help. No matter the wall installation, the SMART ensures perfection for each and every step.

SMART

HANDS-FREE MEANS SPEED AND EFFICIENCY

Avoid the fiddly process in future! The SMART allows you to keep both hands free, which means you can work quickly and efficiently. While it projects the exact laser cross, you can concentrate on your work.





It takes no time at all to mark the area that you want to paint with the SMART.



When wallpapering, simply lay the length of

SMART

HIGH PERFORMANCE YET SIMPLE TO USE

With the SMART, convenience is very much emphasized. We made its design selfexplanatory on purpose, making it simple even for first-time users to use this sophisticated professional technology. Thanks to its long operating time, the SMART will also be happy to "put in overtime".



The clearly visible laser lines begin in front of the device, which is ideal when you are laying tiles or other flooring.

Included:





One movement with the rotary control switch is all it takes for the horizontal and vertical laser lines to become visible. It could not be more simple.

OPTIONAL ACCESSORIES
KST Crank tripod
FST Compact Tripod
UH Universal holder
GA-SET Threaded adapter-set for tripods
LB RED Laser Visibility glasses
ZS RED Target plate

e SMART	MART wallpaper along the vertical line.			
SMART Crossline Laser Specifications				
Max. Mea	surement tolerance	+/- 0.50 mm/m		
Colf lovelling range		1/ 20		

Self-levelling range	+/- 3°
Operating range (radius)	10m*
Operating temperature	-10°C to +50°C
Tripod adapter	1/4°
Power supply	2 x 1.5V (AA) batteries
Operating time (at 20°C)	20h
Laser Class	2
Output power	< 1.0mW
Wavelength	635 nm
Dimensions	97 x 71 x 85 mm

For further information please call or email us

GSR Laser Tools Unit 7 / 7 Prindiville Drive • Wangara WA 6065 Ph: 08 9409 4058 sales@gsrlasertools.com.au • www.gsrlasertools.com.au